

OPzV Standby Power

Eternity Technologies valve regulated lead-acid batteries for the standby power market. With an innovative Gel-Technology design Eternity Technologies OPzV batteries have a reliable maintenance-free and leakage-free construction.

N Part of our Network Power range

Features

- High energy density
- Robust tubular positive electrode design, compliant with DIN 40742
- Low self discharge rate allows for up to 2 years shelf life
- Operating temperature -20°C to +55°C
- 20 year float life at 20°C (68°F)
- EUROBAT design life: Long Life > 12 years
- Fully recyclable with low CO₂ footprint



Applications

- Telecommunications/ Mobile Phone Stations
- Traffic Systems
- UPS Systems
- Emergency Lighting
- Electrical Switching



OPzV Standby Power

DIN Cell Type	Plate (Ah)	Length (mm)	Width (mm)	Height over lid (mm)	Height over pillar (mm)	Typical max weight (kg)	Capacity (Ah) C10 - 1.8V Cell at 20°C
4 OPzV-ET 200	50	105	208	367	392	18.4	225
5 OPzV-ET 250	50	126	208	367	392	22.2	280
6 OPzV-ET 300	50	147	208	367	392	26.2	335
5 OPzV-ET 350	70	126	208	483.5	509	30.7	415
6 OPzV-ET 420	70	147	208	483.5	509	36.2	500
7 OPzV-ET 490	70	168	208	483.5	509	41.7	580
6 OPzV-ET 600	100	147	208	656	681	50.0	750
8 OPzV-ET 800	100	212	193	657	682	66.3	1010
10 OPzV-ET 1000	100	212	235	659	684	81.7	1250
12 OPzV-ET 1200	100	212	277	658	683	97.0	1510
12 OPzV-ET 1500	125	212	277	809	834	111.9	1650
16 OPzV-ET 2000	125	215	400	784	809	155.6	2200
20 OPzV-ET 2500	125	214	489	782	807	190.1	2740
22 OPzV-ET 2750	125	214	578	784	809	216.4	3025
24 OPzV-ET 3000	125	214	578	784	809	226.2	3300
26 OPzV-ET 3250	125	214	578	784	809	236.0	3575


VO option available
Horizontal installation possible

H1: Height over lid
H2: Height over pillar
M10 threaded terminal
Torque: 23Nm


Not to scale




**4 OPzV-ET 200 to
6 OPzV-ET 600**



**8 OPzV-ET 800 to
12 OPzV-ET 1500**



16 OPzV-ET 2000



**20 OPzV-ET 2500 to
26 OPzV-ET 3250**